

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 June 2002 (27.06.2002)


PCT

(10) International Publication Number
WO 02/49691 A2

- (51) International Patent Classification⁷: **A61M** (74) Agent: **THOMAS, John, A.**; Glast, Phillips & Murray, P.C., 13355 Noel Road, Suite 2200, Dallas, TX 75240-6657 (US).
- (21) International Application Number: PCT/US01/50102
- (22) International Filing Date: 21 December 2001 (21.12.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 09/745,905 21 December 2000 (21.12.2000) US
- (71) Applicant and
(72) Inventor: **GILLESPIE, Richard, D., III** [US/US]; 6136 FM 1616, Athens, TX 75751 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent

[Continued on next page]

(54) Title: AUTOMATIC MIXING AND INJECTING APPARATUS



(57) Abstract: An automatic mixing and injecting apparatus comprises a syringe assembly (400) within a housing (100). The syringe assembly (400) has a chamber (425) for holding a liquid, which can be a liquid medicine or a solvent. A second chamber (460) may hold a dry medicine. The second chamber (460) is releasably sealed with respect to the first chamber (425). A spring-operated plunger (300) forces liquid from the first chamber (425) and causes the releasable seal (430) to disengage when the needle (540) has entered the recipient. At this time, the liquid flows through the second chamber (460) and dissolves any dry medicine in that chamber (460). A releasable coupling (340) disengages the plunger (300) from the driver spring (500) and allows the plunger (300), syringe assembly (400), and needle (540) to retract under the urging of a return spring (505).

WO 02/49691 A2